


DC252H-XX-YY

2x250W 24 or 48Vdc powered 70/100V transformerless direct output amplifier



GENERAL DESCRIPTION

Thanks to our transformerless direct output solution, the DC252H digital power amplifier module provides a unique sound, with large frequency response and a better intelligibility for public address systems. The high efficiency power supply enables a fast dynamic. All protections, over current and over temperature are included, insuring a high reliability.

APPLICATIONS

Public address system
Rack mounted amplifier system
Professional audio system
Security audio system

AUXILIARY FUNCTIONS

Enable command
Protect output monitor
Clip detect output
Regulated auxiliary voltage
Selectable power output limiter
Compatible for line impedance monitoring

OPTIONS

24Vdc input or 48Vdc input

KEY FEATURES

DC input 24 Vdc typical	18 to 30Vdc
DC input 48 Vdc typical	36 to 60Vdc
Power/40Ω	2x250Wrms
Load	From 4Ω to open
Frequency response (-3dB)	3Hz to 35KHz
THD+N(1KHz,10W,100Ω)	< 0.04%
Total system efficiency (2X250W/40Ω/24 or 48Vdc)	> 89.3%
Total idle consumption (24Vdc)	< 14.5W
Total idle consumption (48Vdc)	< 14W
Output impedance	< 50mΩ
Fully protected	OTP and OCP
Size	215x80x38mm
Weight	480g

Designed and manufactured in France