

ACL501H

1x500W AC powered 70/100V transformerless direct output amplifier



GENERAL DESCRIPTION

Thanks to our transformerless output solution, the ACL501H digital power amplifier module provides a unique sound, with large frequency response and a better intelligibility for public address systems. The high efficiency power supply enables a fast dynamic response and its automatic 115/230Vac selection make the module compatible with all world mains. All protections, over current and over temperature are included, insuring a high reliability.

APPLICATIONS

Public address system Rack mounted amplifier system Professional audio system Security audio system

AUXILIARY FUNCTIONS

Enable command Protect output monitor Clip detect output Regulated auxiliary voltage Selectable power output limiter

Compatible for line impedance monitoring

OPTIONS

500Wrms or 150Wrms power limiter

KEY FEATURES

Universal AC input (automatic selection) Power/20 Ω Load Available limiters Frequency response (-3dB) THD+N(1kHz,10W,50 Ω) Total system efficiency (200W/50 Ω /230Vac) Idle consumption (230Vac) Output impedance Fully protected Size Weight

100-240Vac

500Wrms From 4Ω to open 150Wrms 3Hz to 35kHz < 0.04% > 93%

< 10W < 50mΩ OTP and OCP 215x80x38mm 360g

Designed and manufactured in France